

Feature Overview

- RFID LF tag in Isocard format
- PVC laminated material
- White and personalized colour
- Copper internal antenna, round or oval shaped
- Operating temperature -25 +50°C
- Storage temperature -25 +50°C
- 5,8 gram weight
- Standard ISO7816
- High quality Isocard, reliable and extremely flat
- Size 85 X 54 X 0,76 mm



Applications

- Contactless and automatic ID
- Access Control
- Logistics
- Payment Systems
- Robotics
- Automatic Machines
- Traceability
- Sensor

High quality Isocard, reliable and extremely flat, to ensure a perfect result for customer personalization with different printing technologies. Mainly indicated for Access Control applications.

Models

P. Number	Frequency	Chip	Type	Notes
610W001	125 kHz	EM4200	ro 64bit	Oval antenna close to isocard edge
691W001	125 kHz	TK4100	ro 64bit	Oval antenna close to isocard edge
602W001	125 kHz	EM4550	rw 1kbit	Oval antenna close to isocard edge
611W001	125 kHz	ATA5577	rw 363bit	Oval antenna close to isocard edge
623W001	125 kHz	HS256	rw 256bit	Oval antenna close to isocard edge
624W001	125 kHz	HS2K	rw 2Kbit	Oval antenna close to isocard edge

Available with circular antenna.

Available Combo versions with magnetic stripe, contact chip and HF or UHF RFID technologies.

Available with other ICs.

Information from manufacturer specifications.

Specifications are subject to change without prior notice.