

**Feature Overview**

- RFID LF and HF in keychain format
- Polycarbonate housing
- Blue translucent colour
- Operating temperature -20 +75°C
- Storage temperature -40 +80°C
- Available in read only or read and write version
- IP67 Protocol



**Applications**

- Contactless and automatic ID
- Automation
- Logistics
- Access control
- Gyms
- Automatic machines
- Traceability
- Recreation centers

Especially in the stylized shape and blue colour remains a unique reference. Mainly indicated for industrial and civil applications, automation machines and access control.  
Also available in different colour.

**Models**

P. Number	Frequency	Chip	Type	Diameter	Thickness	Notes
601A911	125 kHz	EM4100	ro 64bit	49 X 33 mm	7 mm	
691A911	125 kHz	TK4100	ro 64bit	49 X 33 mm	7 mm	
602A911	125 kHz	EM4550	rw 1kbit	49 X 33 mm	7 mm	
611A911	125 kHz	T5577	rw 330bit	49 X 33 mm	7 mm	
607A911	13,56 MHz	MIFARE 1K	rw 1kbyte	49 X 33 mm	7 mm	
629A911	13,56 MHz	I-CODE 2	rw 1kbit	49 X 33 mm	7 mm	

Also available with other chip.  
Information from manufacturer specifications.  
Specifications are subject to change without prior notice.