


RFID Reader for LogIn applications

Wide set of rfid modules studied to be used on board of automatic machines or PC systems for automatic authentication of people. The series could be provided with or without retention of tag. Some models can also, read/write ISOcard with contact chips.



Description	LogIn ø22 a prossimità	LogIn a prossimità	LogIn ø30 a prossimità	LogIn Industriale a prossimità	LogIn a inserimento Isocard RFID	LogIn a inserimento chiave
P/N	A2M22	A2098P	A2M30	A25035	TWN4	A2098C
Frequency	125KHz e 13,56MHz	125KHz e 13,56MHz	125KHz e 13,56MHz	125KHz e 13,56MHz	125KHz e 13,56MHz	125KHz e 13,56MHz
Dimensions	ø29 x 9 mm Foro ø22 a pannello	98 x 64 x 37 mm	ø30 x 45 mm Foro ø30 a pannello	50 x 35 x 20 mm	88 x 68 x 9 mm	98 x 64 x 37 mm
Interface	USB VC-USB ET-RS232	USB VC-USB ET-RS232	USB VC-USB ET-RS232	USB VC-USB ET-RS232	USB VC-USB ET-RS232	USB VC-USB ET-RS232
Antenna	Internal	Internal	Internal	Internal	Internal	Internal
Voltage Supply	5Vdc o 9-34Vdc	5Vdc o 8-14Vdc	5Vdc o 8-14Vdc	5Vdc o 8-14Vdc	5Vdc	5Vdc o 8-14Vdc
Temperature Range	-20 +55 °C	-20 +55 °C	-20 +65 °C	-20 +65 °C	-25 +70 °C	-20 +55 °C
Digital I/O	2	2	2	-	-	2
Indications	-	-	Led	Led	Led & Buzzer	Led
Connectors	Cable with connector	Cable with connector	IDC connector	M8 IP65	Cable with connector	Cable with connector
R/W Distance	Up to 5 cm	Up to 5 cm	Up to 5 cm	Up to 5 cm	Up to 5 cm	Up to 5 cm
Standard	FDX-Iso14443A/B-Iso15693	HDX-Iso14443A/B-Iso15693	HDX-FDX-Iso14443A/B-Iso15693	HDX-FDX-Iso14443A/B-Iso15693	HDX-FDX-Iso14443A/B-Iso15693	HDX-FDX-Iso14443A/B-Iso15693
Protection	IP65	IP65	IP65	IP65	IP54	IP65

All, RFID Reader for LogIn Application, are available with Ethernet Interface, with external accessories